DEWBU®

# 12V Power Bank


Model: DB-0125

## User Guide

The related safety warnings and all instructions must be observed, otherwise you may get a shock hazard, fire or serious injury. Before using this product, read manual carefully and keep it for future reference.

12-MONTH WARRANTY

## 1. Battery Usage Instructions



❶ Smart Digital Display
Display shows the remaining power and charging status with precision.

❷ DC Output: 12V/1.5A

❸ USB Type-C
Input: 5V/9V/12V⎓3A Max
USB Type-C
Output: 5V⎓1.5A

❹ Power Display
Short press to display battery level.

## 2. Battery Specifications

DEWBU Power Bank

| Model | DB-0125 |
|---|---|
| Battery Energy | 10.8V, 54Wh (5000mAh) |
| USB Type-C Output | 5V⎓1.5A (8700mAh) |
| USB Type-C Input | 5V/9V/12V⎓3A Max |
| DC Output | 12V⎓1.5A (4300mAh) |

Before first use, make sure the battery has enough power by charging it fully, only needs approximately 4 hours with an 18W charger (about 7 hrs with 10W, about 12 hrs with 5W, about 22 hrs with 2.5W).
Please insert the DC plug to the bottom to prevent poor contact.

⚠ Attention Please: The DB-0125 12V battery can only be used for the 12V heated apparel and charging mobile devices.

## 3. Attention

- Please remember to charge your battery every 3 months when leaving the battery unused.
- Please avoid direct sunlight or humid environments.
- Temperature of battery charging: 32°F-122°F( 0℃～50℃).
- Temperature of battery discharging: 14°F-140°F(-10℃～60℃).
- Temperature of storage: -4°F-113°F(-20℃～45℃).
- Altitude not higher than 2000m (air pressure not less than 80kPa).

## 4. Tips & Warnings

- Please remove battery from apparel when you do not wear it.
- DO NOT disassemble, modify, or repair any part of the product, replacement of a battery with an incorrect type may defeat a safeguard.
- DO NOT dispose of used battery packs into a fire or a hot oven, or mechanically crush or cut off a battery, which may result in an explosion.
- DO NOT leave a battery in extremely low air pressure or extremely high temperature surrounding environment(sunshine, fire, or hot surface), which may result in an explosion or flammable liquid or gas leakage.
- DO NOT open, Crush or Heat Above 104°F(40°C).

E-mail:support@dewbu.com

CONFORMS TO UL Subject 2056
Conf. to UL STD. 62368-1
Cert. to CSA STD. C22.2 No. 62368-1
Intertek 5023054
CAN ICES-003 (B) / NMB-003 (B)

Made in China